REV. 07/01

Mueller Steam Specialty


Model: 351M-N

| WORKING PRESSURES - NON-SHOCK | | | | |
|-------------------------------|------------------|--|--|--|
| STEAM | WOG | | | |
| 200 PSI @ 350° F | 300 PSI @ 150° F | | | |

Cast Bronze Screwed End "Y" Type Strainer

351M-N Class 150





Model 351M-N

SERVICE RECOMMENDATIONS

This model can be used extensively to strain foreign matter from pipelines and provide inexpensive protection for costly pumps, meters, vavles and similar equipment.

SCREENS

Model 351M-N is furnished with 20 mesh [1/32" (.80mm) openings] for water service.

CONSTRUCTION

The model has machined screen seat in the body and cap to assure perfect screen alignment and easy reassembly when servicing is required. Commercial strainers in ASTM B62 Bronze. All sizes feature a straight threaded, gasketed cap.

SELF CLEANING

Self cleaning is accomplished by opening the valve or cap connected to the blowoff outlet.

INDIVIDUALLY HYDROSTATICALLY TESTED.

MATERIALS:

Body and Cap Screen Gasket Bronze ASTM B62 304 Stainless Steel ASTM A240 PTFE

DIMENSIONS AND WEIGHTS

| size | in | 1/2" | 3/4" | 1" | 1-1/4" | 1-1/2" | 2" |
|--------|------|---------|-------|-------|---------|--------|--------|
| | mm | 15 | 20 | 25 | 32 | 40 | 50 |
| Α | in | 2-15/16 | 3-3/8 | 4-1/4 | 4-13/16 | 5-5/16 | 6-8/16 |
| В | in | 1-7/8 | 2-1/4 | 2-7/8 | 3-3/8 | 3-3/4 | 4-1/2 |
| С | in | 3 | 3-7/8 | 4-1/4 | 5-1/2 | 6-5/16 | 7-7/8 |
| Weight | lbs. | .51 | .75 | 1.12 | 2.18 | 2.68 | 4.36 |

Approximate Dimensions and Weights. Apply For Certified Drawings.